

80MM Thermal Printer

(Model No.: OCPP-802)

FEATURE:

- Loading paper easy, waterproof, oil proof, dustproof
- 230mm/sec high speed printing image and characters, best printing quality and reliable performance
- Support print prompt and error alarm
- Support black mark sensor, reprint function
- Compatible with EPSON ESC/POS
- Support 256K bytes NV logo download store and print
- Support printer status monitor function, control printer's status at any time.
- Support cash drawer driving

SPECIFICATION:

Printing method	Direct thermal
Character size	ANK,FontA:12*24dots,FontB:9*17dots
Column capacity:	576dots/line OR 512dots/line
Character set	PC347 (Standard Europe)、Katakana、PC850 (Multilingual)、PC860 (Portuguese)、PC863 (Canadian-French)、PC865 (Nordic)、West Europe、Greek、Hebrew、East Europe、Iran、WPC1252、PC866 (Cyrillic#2)、PC852 (Latin2)、PC858、IranII、Latvian、Arabic、PT151 (1251)
Barcode	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODABAR/ITF/CODE39/CODE93/CODE128
Printing speed	230mm/sec
Receive buffer	128k bytes
NV flash buffer	256K bytes
Paper width	79.5±0.5mm
MCBF(life)	100km
Printing command	Compatible with ESC/POS
Cash drawer control	DC 12-24V/1A
Paper thickness	0.06-0.08mm
Cutter	Manual Cutter
Roll paper	79.5±0.5mm* φ83mm
Interface	Serial/parallel/ USB/LAN
Driver	Win 9X/Win ME/Win 2000/Win 2003/Win NT/Win XP/Win Vista/win 7/Linux
Power supply	DC24V/2.5A
Power adapter input	AC 110V/220V, 50~60Hz ;output: DC 24V/2.5A
Dimension	190x145x150mm
Weight	3.5kg


Different Angles:



Different Parts:



Long lifetime printing machine, excellent mainboard, ultra durable big gear, support Linux/Windows 7 system driver, various international languages.




Different Interfaces:



Available Power Plug:



Packing details:



One piece in a single box, 6 pieces into an out carton. Carton size 70*34*45cm.