

## 433Mhz or Bluetooth Wireless 2D Barcode Scanner With Cradle

(Model: OCBS-W231-4/W231B)

## Features:

- 433Mhz Wireless communication distance outdoor 300m,indoor 100m; Bluetooth wireless communication distance outdoor 20m, and 10m indoor;
- 2. Equipped with communication and charging base
- 3. Soft plastic cover to protect the lens and outline greatly enhances the anti-drop performance;
- 4. Barcode on computers' and mobile phones' screen can be scanned;
- 5. No driver, plug and play;
- 6. Can store more than 10,000 pieces of data;
- Multiple scanners can be connected to one receiver (433mhz).



## Parameters:

Aiming Light Source617 nm LEDLighting Light Source625 nm LEDScanning Angle39° (H) x 25° (V)Rotation Angle0 - 360°Elevation Angle± 65°Tilt Angle± 60°Print ContrastHigher than 25%
Scanning Angle $39^{\circ}$ (H) x 25° (V)Rotation Angle $0 - 360^{\circ}$ Elevation Angle $\pm 65^{\circ}$ Tilt Angle $\pm 60^{\circ}$
Rotation Angle $0 - 360^{\circ}$ Elevation Angle $\pm 65^{\circ}$ Tilt Angle $\pm 60^{\circ}$
Elevation Angle $\pm 65^{\circ}$ Tilt Angle $\pm 60^{\circ}$
Tilt Angle $\pm 60^{\circ}$
Print Contrast Higher than 25%
1D UPC/EAN, UPC/EAN with supplementals, BooklandEAN, ISSN, UCC Coup
Extended Code, Code128, GS1-128, ISBT 128, Code 39, Code 39 Full ASC
Trioptic Code 39, Code 32, Code 93, Code11, Matrix 2 of 5, Interleaved 2 of
Discrete 2of 5, Codabar, MSI, Chinese 2 of 5, GS1 Data Barvariants, Korear
of 5, ISBT Concat
2D PDF417, MicroPDF417, Composite Codes, TLC-39,Data Matrix, Maxicode, C
Code, MicroQR, Aztec
Interface USB (Wirelless receiver cable)
Communication 433mhz: Inside: 100m; Outside: 300m (Max)
distance Bluetooth: Inside: 10m; Outside:20m (Max)
Operating Temperature -10 deg C - 45 deg C
Storage Temperature -20 deg C - 65 deg C
Operating Humidity 5%-85%
Storage Humidity 5%-95%
Durability Withstands multiple 1.5m drops to concrete
Input Power DC 5V, 280mA
Charging time 6h

Page 1 of 1

## OCOM Technologies Limited

Address: Unit701,Block14,Zhongxing Industrial Park,Chuangye Road



Nanshan District, Shenzhen 518054, China; Web: www.ocominc.com,www.ocomtech.com.cn;

Battery	1500mAh			
Lumination	Inside: 3.000 LUX max;	Outside sunlight: 86000LUX	( max	
IP Grade	IP42			
DECODE RANGES				
Typical Performance*		Typical Working Ranges		
		HD Focus Range		
Bar Code Type	Symbol Density	Near	Far	
Code 39	5.0 mil	5mm	90mm	
100% UPCA	13.0 mil	8mm	200mm	
Code 39	20.0 mil	8mm	250mm	
PDF 417	6.8 mil	5mm	95mm	
Data Matrix	10.0 mil	5mm	110mm	
QR Code	20.0 mil	10mm	150mm	
Resolution 1D Code 39	4 mil			
Resolution 2D Data Matrix	10 mil			
Material	ABS+PC			
Dimension	Scanner (70*95*168mm)	Base(145*112*74mm)		
Net Weight	Scanner 185g Base 186g			
Ordering Info.	dering Info. 433MHz wireless communication (OCBS-W231-4)			
	Bluetooth communication (	OCBS-W231-B)		