

3 Inch Portable Mini Bluetooth Thermal Receipt Printer

(M/N:OCP-P-M084)



- Support Windows, Java, Android or IOS
- Provide SDK for Android and IOS, driver for Windows PC
- Bluetooth, USB and RS232 communication
- 2000mAh high capacity battery
- Higher print speed 80mm/sec
- 50km TPH Life
- A variety of 1D and 2D code supported
- Built-in buzzer more easily for user get the printer status

Printing	
Printing method	Direct thermal
Print width	72mm
Column capacity	8dots/mm, 576dots/line
Printing speed	80mm/s
Interface	Bluetooth、USB、Serial
Printing paper	79.5±0.5mm×φ40mm
Line spacing	3.75mm (Adjustable by commands)
Column number	58mm paper: Font A - 32 columns/Font B - 42 columns/ Chinese,traditional Chinese - 16 columns
Character size	ANK , Font A : 1.5×3.0mm (12×24 dots) Font B : 1.1×2.1mm (9×17 dots) Chinese,traditional Chinese:3.0×3.0mm (24×24 dots)

OCOM Technologies Limited

Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan,
Shenzhen 518059, China;

Website: www.ocominc.com, www.possolution.com.cn;

E-mail: ocom@ocominc.com;

Tel/Fax: +86.755.8605.3207;



Barcode Character	
Extension character sheet	PC347(Standard Europe), Katakana, PC850(Multilingual), PC860 (Portuguese) , PC863 (Canadian-French) , PC865 (Nordic) , West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2) , PC852 (Latin2) , PC858, IranII, Latvian, Arabic, PT151 (1251)
Barcode types	UPC-A/UPC-E/JAN13 (EAN13) /JAN8 (EAN8) /CODE39/ITF/CODABAR/CODE93/CODE128/QR/PDF417
Buffer	
Input buffer	32k bytes
NV Flash	64k bytes
Power	
Power supply	Input : AC 110V/240V, 50 ~ 60Hz
Power source	Output : DC 9V-2A
Physical characteristics	
Weight	0.19KG
Dimensions	111×88×41mm(D x W x H)
Environmental Requirements	
Work environment	Temperature (0 ~ 45) humidity(10 ~ 90%)
Storage environment	Temperature(-10 ~ 60℃) humidity(10 ~ 90%)
Reliability	
Printer head life	50KM