Handheld Anroid POS Terminal for Payment

(M/N:POS-Z90)

Feature:

- Android 5.1 operating system;
- Quad core Qualcomm MSM8909;
- 5.0 inch touch screen;
- Long standby battery capacity is 2800mAh;
- 58mm thermal receipt printer;
- 5 million pixels camera;
- 2G /3G/4G Wifi, Bluetooth communication;
- Optional fingerprint reader;
- Integrated magnetic card reader,induction IC card reader and contact IC card reader;
- Passed the EMV L1 L2,PCI and PBOC bank payment certification.

Application :

apply chain supermarkets, restaurants, convenience stores,clothing store, premises, bakery, cashier, pay, enters sells saves the business management function.

Technical Specification:

Basic Information	
Operating system	Android 5.1
CPU	Quad core Qualcomm MSM8909
RAM	RAM:1GB
Extended stored	FLASH:8GB
Display screen	5.0 inch
Touch screen	Capacitive touch screen, support the electronic signature
Battery	Lithium battery 2800mAh, 7.4 V
Power supply	Input: 100-240VAC; Output: 5VDC, 2A
Bluetooth	Bluetooth 4.0
Camera	5 mega-pixel camera
Positioning function	GPS AGPS WLAN for Positioning

Product specifications are subject to change without prior notice.

Together We Quest For The Best

OCOM Technologies Limited

Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan,
Shenzhen 518059, China;
Website: www.ocominc.com, www.possolution.com.cn;
E-mail: ocom@ocominc.com;
Tel/Fax: +86.755.8605.3207;

Printer	58mm thermal printer with 30mm diameter Paper roll
MDM	Mobile Device Management
Interface	Micro USB (mini USB for factory)
Cradle （optional）	WIFI station, charging, qr code scanner
POS Function	
Magnetic card reader	Full track magnetic card reader Support ISO7811/7812,AAMVA protocol
IC card read-write	Support ISO7816 protocol
Non-contact card reader	Support ISO/IEC 14443 Type A&B, ISO18092, Mifare, felica card, in line with the EMV/PBOC PAYPASS specification
PSAM Card	Bank security payment chip card
Certification	Unionpay card acceptance terminal network detection PCI certification EMV/PBOC3.0 L1 and L2 certification EMV/qPBOC3.0 L1 and L2 certification Unionpay intelligent safety standards point-of-saleterminals
Network Parameters	
Network Type	GSM, WCDMA, TD-SCDMA, FDD-LET, TDD-LTE
Network Spectrum	GSM850/900/1800/1900
	WCDMA2100/1900/900/850
	TD-SCDMA B34/B39
	FDD-LTE B1/B2/B3/B4/B5/B7/B8/B20
	TDD-LTE B38/B39/B40/B41
WLAN	IEEEE802.11.b/n/g
Sam Slot	2 (one is sam&sim combined)
Sim Slot	2 (one is sam&sim combined)
Physical Parameters	
Size	191mm×80mm×46mm
Weight	650g
Operating Temp	-20°C ~ 60°C
Storage Temp	-40°C ~ 80°C

Product specifications are subject to change without prior notice.

Together We Quest For The Best

OCOM Technologies Limited

Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan,
Shenzhen 518059, China;
Website: www.ocominc.com, www.possolution.com.cn;
E-mail: ocom@ocominc.com;
Tel/Fax: +86.755.8605.3207;

Humidity	10%~90% RH non-condensing

Product specifications are subject to change without prior notice.

Together We Quest For The Best

There are four card slots

Standard Configuration
TF Slot   *1
SAM Slot *1
SIM Slot *2

or

Optional
TF Slot   *1
SAM Slot *2
SIM Slot   *1

Product specifications are subject to change without prior notice.

Together We Quest For The Best