

# 58mm Thermal Printer With Built-in Power Supply

(OCPP-58X)



# **Product Introduction:**

OCPP-58X is a well-designed economic printer for common thermal bill printing, It is adopt built-in power supply,not only can save space,but also easy for users to configure and use the printers. It's a very good choice for economical printing.

## **Product Features :**

- •Simple and fashion, With solid material, exquisite workmanship.
- •Easy paper install structure, simple and convenient to operate
- •Built-in power supply design, to save space and more convenient to configure;
- •Support multi language print, suitable for users all over the world;
- •Support download and print LOGO&graphics ;

#### **Application Area :**

Shopping malls, restaurants, stores, warehousing, taxation, banking, medical, postal

Product specifications are subject to change without prior notice.



# **Parameters :**

Items		Parameters
Print parameters	Printing Method	Thermal Line
	Printing Width	48MM
	Resolution	384dots/Line (8dots/mm, 203dpi)
	Printing Speed	90mm/Second
	Interface Type	USB, Parallel
	Line Spacing	3.75 mm (Can adjust line spacing by command)
	Line No.	Font A:32 character /Line
		Font B:42 character/Line
		Simple, traditional Chinese-16 lines
	Character	Standard GB2312 simplified Chinese Fonts
	Character Size	ANKcharacter, Font A: 1.5×3.0mm (12×24dots)
		Font B : 1.1×2.1mm (9×17dots) Simplified/Traditional
		Chinese: 3.0×3.0mm(24×24 dots)
Bar code Character	Extended	PC437/Katakana/PC850/PC860/PC863/PC865/WestEurope/
	character set	Greek/Hebrew/EastEurope/Iran/WPC1252/PC866/PC852/P
		C858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/T
		haiVietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251
		)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
	Bar code	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)CODE39/ITF/
		CODABAR/CODE93/CODE128
Graphics printing	Graphics printing	Supports bitmap download and print
Paper	Туре	Thermal Roll
	Width	57.5±0.5mm
	Diameter	≤60mm
	Feed Method	Easy feed(Clamshell feed)
Print commands	Commands	ESC/POS
Power	Power Adaptor	Input: AC 100V-240V,50-60Hz
		Output: DC 12V/2.6A
	Casher Drawer	DC 12V/1A
	output	
Buffer	Input Buffer	32 KB
	NV Flash	64 KB

Product specifications are subject to change without prior notice.

OCOM Technologies Limited Address:3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan, Shenzhen 518059, China; Website: www.ocominc.com, www.possolution.com.cn; E-mail: ocom@ocominc.com; Tel/Fax: +86.755.8605.3207;



Product specifications are subject to change without prior notice.