

## 2 Inch Direct Thermal Label Printer (M/N:OCBP-201)

- ❖ USB or USB+Bluetooth or USB+WIFI Interface for optional
- ❖ Automatic paper checking function
- ❖ Temperature adaptive control
- ❖ Support receipt mode and label mode switching
- ❖ Compatible with TSPL and ESC/POS command
- ❖ Compact and sleek design for stylish counters



Printing method	Direct thermal
Resolution	203DPI
Command	TSPL and ESC/POS
Mode switching	Support receipt mode and label mode switching (Command:HEX:1F 1B 1F 02 20 n 0D 0A,n=31/30.default n=30)
Print width	20-60mm
Printing speed	MAX:101mm/s; MIN:50.8mm/s
Memory	DRAM: 256kb FLASH: 576kb
Printhead temperature	Thermistor
Paper exists detection	Micro switch
Interface	USB or USB+Bluetooth or USB+WIFI
Paper presence detection	Paper presence detection
Barcode	CODE128、EAN128、ITF、CODE39、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPC-E、UPCE+2、UPC-E+5、CPOST、MSI、MSIC、PLESSEY、ITF14、EAN14 Qrcode、DM Code、PDF417
Enlargement & rotation	(0°、90°270°、360°) 1 to 10 times enlargement in both direction; 0°、90°、270°、360° rotation
Image	Monochromatic PCX, BMP image files can be load to FLASH
Paper type	Paper roll, sticker, adhesive sticker, etc
Paper width	20mm~60mm
Roll external	MAX 80mm
Roll inner diameter	MIN 25mm
Paper off type	Tear off
Power supply input	DC12V, 3A
Work environment	5~45℃, 20—80%RH(no condensation)
Storage environment	-40~55℃, ≤93%RH (40℃)

**Product specifications are subject to change without prior notice.**

**Together We Quest For The Best**

**OCOM Technologies Limited**

**Address:** 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan,  
Shenzhen 518059, China;

**Website:** [www.ocominc.com](http://www.ocominc.com), [www.possolution.com.cn](http://www.possolution.com.cn);

**E-mail:** [ocom@ocominc.com](mailto:ocom@ocominc.com);

**Tel/Fax:** +86.755.8605.3207;

---

