OCOM Technologies Limited

Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan,

Shenzhen 518059, China;

Website: www.ocominc.com, www.possolution.com.cn;

E-mail: ocom@ocominc.com; **Tel/Fax:** +86.755.8605.3207;



Thermal Barcode Label Printer

(Model No.: OCBP-T31)

Features:

- Label paper auto position;
- Support Paper out sensor;
- Support open cover sensor;
- Support label interval sensor;
- Built-in power supply saves office space
- 4MB DRAM and 4MB FLASH
- Compatible with plenty of label software;
- Support BMP, PCX, BAC images download;
- Support USB or USB+Bluetooth;
- Support PDF417, QR CODE, DOTMATRIX;



Specifications:

| Printer Model | OCBP-T31 |
|----------------------------------|---|
| Resolution | 203 DPI (8 dot/mm) |
| Printing Method | Direct Thermal |
| Printing head temperature sensor | Thermal sensitive resistance |
| Printing head position sensor | Micro switch |
| Paper exists detection | Photoelectric sensor |
| Printing Speed | 127 mm / sec (max); 50.8mm/sec (min) |
| Printing Width | 16 mm ~ 76 mm |
| Media | Media Type: Paper roll, sticker, label fold, etc. Media diameter: Inner dia:25mm; Outer dia: 80mm |
| Internal font | FONT 0 to FONT 8; Commonly used in single-byte fonts |
| Enlargement & rotation | 1 to 10 times enlargement in both directions; 0 Degree , 90 Degree, 180 Degree, 270 Degree, 360 Degree rotation |
| Paper off type | Tear off |
| Memory | 4MB Flash Rom, 4MB DRAM |
| Image | Monochromatic PCX, BMP image files can be load to FLASH, DRAM |

Product specifications are subject to change without prior notice.

OCOM Technologies Limited
Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan, Shenzhen 518059, China;
Website: www.ocominc.com, www.possolution.com.cn;
E-mail: ocom@ocominc.com;
Tel/Fax: +86.755.8605.3207;



| Barcode | CODE128, EAN128, ITF, Code39, Code93, EAN13, EAN13+2, EAN13+5, EAN8, EAN8+2, EAN8+5, CODABAR, POSTNET, UPC-A, UPCA+2, UPCA+5, UPC-E, UPCE+2, UPCE+5, CPOST, MSI, MSIC, PLESSEY, ITF14, EAN14, PDF417, QR CODE, DATMATRIX |
|-------------|--|
| Interface | USB or USB+Bluetooth |
| Power | Built-in power supply input AC110V-240V |
| Environment | Operating Temperature: 5 Degree C to 45 Degree C Storage Temperature: -40 Degree C to 55 Degree C Operating Humidity: 20% ~ 80%, non-condensing, Free air Storage Humidity: <=93%(40 Degree C), non-condensing, Free air |
| Dimension | Size: D230mm * H163mm *W152mm |
| Net Weight | 1.48kg |

Picture Show:





Product specifications are subject to change without prior notice.

OCOM Technologies Limited
Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan, Shenzhen 518059, China;
Website: www.ocominc.com, www.possolution.com.cn;
E-mail: ocom@ocominc.com;
Tel/Fax: +86.755.8605.3207;





Product specifications are subject to change without prior notice.