

OCOM Technologies Limited

Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan,
Shenzhen 518059, China;

Website: www.ocominc.com, www.possolution.com.cn;

E-mail: ocom@ocominc.com;

Tel/Fax: +86.755.8605.3207;



Handheld Laser Barcode Scanner

(Model No.: OCBS-L009)

FEATURE:

- 200scan/sec high scan rate and long reading distance;
- Excellent decode capability;
- KBW, RS232 and USB supported;
- Durable construction combined with future-proofing;
- Grey and black color for option;



SPECIFICATION:

Performance Characteristics	
Light Source:	650nm visible
Scan Rate:	200 scans per second
CPU	32 bit
Reading Distance	2.5 ~600mm (100% UPC/EAN)
Width of Scan	50mm@60mm, 220mm@200mm
Scanner Type:	Bi-directional
Operation mode	triggered
Resolution:	3mil high resolution series / 5mil long depth field series
Print Contrast Minimum:	25%, minimum reflective difference
Decode Capability:	UPC/EAN, UPC/EAN with Supplemental, UCC/EAN 128, Code 39, Code 39 Full ASCII, Trioptic Code 39, Code 128, Code 128 Full ASCII, Coda bar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, RSS variants, Chinese 2 of 5, MSI/Plessey, UK/Plessey, UCC/EAN 128, Chinese code , GS1 Data Bar (RSS) series
Scanning Angle	±65°(tilt); ±60°(pitch); ±42°(yaw)
Physical Characteristics	
Interfaces Supported:	PS2, RS232, USB
Voltage:	5V DC±5%

Product specifications are subject to change without prior notice.

Together We Quest For The Best

OCOM Technologies Limited

Address: 3A01, 4F, Block 2, Nanyou 4th Industrial Park, NanShan Ave, Nanshan, Shenzhen 518059, China;

Website: www.ocominc.com, www.possolution.com.cn;

E-mail: ocom@ocominc.com;

Tel/Fax: +86.755.8605.3207;



Current:	85 mA (Operating); 100 (Max)
Indicator	Beeper, LED
Material	ABS+PC
Stand	Optional
Dimensions:	156*68*83 mm (L*W*H)
Weight:	235g
Color:	Grey and black
User Environment	
Operating Temperature:	0 Degree C~45 Degree C
Storage Temperature:	-40 Degree C~60 Degree C
Humidity:	5%-90% (non-condensing)
Electrostatic Discharge:	Conforms to +/-15KV air discharge and +/-8KV of contact discharge
Ambient Illumination	0 ~ 100,000 LUX
Drop Specifications:	Withstands multiple 1.5m drops to concrete surface
Laser classification	EN60825-1, class 1

Product specifications are subject to change without prior notice.

Together We Quest For The Best